



CINCH CRANKS - Q FACTORS AND CHAINLINES - REV. G

power2max NG/NGeco
 MTB RaceFace
 single with adapter
 (+3mm without adapter)
 (no Flipped Ring)

power2max NG/NGeco
 MTB RaceFace
 double

Crank	RF Spindle code (Length in brackets)	Part Number	Q-Factor (mm)	Chainline RF Direct mount ring 3X 104/64 BCD Spider 1X 104 BCD DH spider (mm)	Chainline BMX 1X Spider (mm)	Chainline 2X 104/64 BCD spider 2X 120/80 BCD spider (mm)	Chainline "Boost" 2X 104/64 BCD Spider (mm)
Next SL - Cinch	RF134 (134.5)	F30030	168	51 57.5 - Flipped Ring	47.5	49.5	52.5
	RF143 (143.5)		177	55.5 62 - Flipped Ring	52	54	57
	RF149 (149.5)	F30033	183	58.5 65 - Flipped Ring	55	57	60
	RF169 (169.5)	F30031	203	68.5 75 - Flipped Ring	65	67	70
	RF189 (189.5)	F30032	223	78.5 85 - Flipped Ring	75	77	80
SixC - Cinch	RF131BM (131.5)	F30036	170	48.5 55 - Flipped Ring	45	47	50
	RF136DH (136.5)	F30034	175	51 57.5 - Flipped Ring	48	49.5	52.5
	RF151DH (151.5)	F30035	190	58.5 65 - Flipped Ring	55	57	60
Turbine - Cinch	RF134 (134.5)	F30030	178	51 57.5 - Flipped Ring	47.5	49.5	52.5
	RF143 (143.5)		187	55.5 62 - Flipped Ring	52	54	57
	RF149 (149.5)	F30033	193	58.5 65 - Flipped Ring	55	57	60
	RF169 (169.5)	F30031	213	68.5 75 - Flipped Ring	65	67	70
	RF189 (189.5)	F30032	233	78.5 85 - Flipped Ring	75	77	80
Atlas - Cinch	RF131BM (131.5)	F30036	173	48.5 55 - Flipped Ring	45	47	50
	RF136DH (136.5)	F30034	178	51 57.5 - Flipped Ring	48	49.5	52.5
	RF151DH (151.5)	F30035	193	58.5 65 - Flipped Ring	55	57	60
Aeffect - Cinch	RXC (135)	NA	173	50-52 56.5-58.5 - Flipped Ring	46.5-48.5	48.5-50.5	51.5-53.5
	XCP (144)	NA	182	54.5-56.5 61-63 - Flipped Ring	51-53	53-55	56-58
	AM83(156)	NA	189	57.5-60.5 64-67 - Flipped Ring	54-57	56-59	59-62
	XCF100 (167)	NA	205	66-68 72.5-74.5 - Flipped Ring	62.5-64.5	64.5-66.5	67.5-69.5
	XCF190 (190)	NA	228	77.5-79.5 84-86 - Flipped Ring	74-76	76-78	79-81